

# ROCKY-538

PICMG Socket 7 66MHz FSB CPU Card with VGA(4MB), DOC

# ROCKY-548

PICMG Socket 7 66MHz FSB CPU Card with DOC



## Feature

- Intel PentiumMMX CPU supports upto FSB 66 MHz
- ATi Rage Mobility-M with 4MB memory
- PC66 SDRAM memory support upto 256MB
- USB, DOC socket integrated

## Feature

- Intel PentiumMMX CPU support up to FSB 66 MHz
- PC66 SDRAM memory support upto 256MB
- USB, DOC socket integrated

## Specifications

<b>CPU Type</b>	Socket-7 base support Intel® Pentium® MMX up to 66 MHz FSB
<b>System Chipset</b>	Intel® 430TX
<b>System Memory</b>	2 x 168-pin DIMM sockets support up to 256MB SDRAM
<b>Display Controller</b>	ATI Rage Mobility-M BUS: AGP 2X V-RAM: 4MB SDRAM Resolution: 1280 x 1024@24-bit DB-15 for VGA
<b>SSD</b>	1 x DiskOnChip™ socket
<b>Ethernet</b>	N/A
<b>I/O</b>	2 x RS-232 1 x PS/2 for Keyboard 1 x PS/2 for Mouse 1 x LPT supports SPP/ECP/EPP mode 2 x USB 1.0 2 x ATA-33 IDE channels 1 x Floppy 1 x IrDA (SIR)
<b>WDT</b>	Software Programmable supports 1~255 sec system reset
<b>E2Key</b>	A non-volatile 1K-bit EEPROM is provided to retain application critical read/write data
<b>ISA Plus™</b>	Yes
<b>Hardware Monitor</b>	Provides CPU Vcore, Vcc, CPU/System fan speed and temperature detecting function
<b>Power Consumption</b>	+12V@70mA, +5V@7A, -12V@20mA, (Pentium® MMX 200MHz with 32MB SDRAM)
<b>Operation Temperature</b>	0~60°C
<b>GW</b>	900g

## Specifications

<b>CPU Type</b>	Socket-7 base support Intel® Pentium® MMX, AMD® K6 up to 66 MHz FSB
<b>System Chipset</b>	Intel® 430TX
<b>System Memory</b>	2 x 168-pin DIMM sockets support up to 256MB SDRAM
<b>Display Controller</b>	N/A
<b>SSD</b>	4 x DiskOnChip™ socket
<b>Ethernet</b>	N/A
<b>I/O</b>	2 x RS-232 1 x PS/2 for Keyboard 1 x PS/2 for Mouse 1 x LPT supports SPP/ECP/EPP mode 2 x USB 1.0 2 x ATA-33 IDE channels 1 x Floppy 1 x IrDA (SIR)
<b>WDT</b>	Software Programmable supports 1~255 sec system reset
<b>E2Key</b>	A non-volatile 1K-bit EEPROM is provided to retain application critical read/write data
<b>ISA Plus™</b>	Designed to enhance the ISA bus drive capability
<b>Hardware Monitor</b>	Provides CPU Vcore, Vcc, CPU/System fan speed and temperature detecting function
<b>Power Consumption</b>	+12V@70mA, +5V@7A, -12V@20mA, (Pentium® MMX 200MHz with 32MB SDRAM)
<b>Operation Temperature</b>	0~60°C

## Ordering Information

- **ROCKY-538TXV-R7**  
PICMG Socket 7 66MHz FSB CPU Card with VGA(4MB), DOC, R7

## Ordering Information

- **ROCKY-548TX-R6**  
PICMG Socket 7 66MHz FSB CPU Card with DOC, R6

## IEI Option

- **CB-USB02** Dual ports USB cable with bracket [page 5-6](#)
- **CF-502** Socket-7 CPU Cooler
- **CF-504** Slim Type Copper Socket-7/370 CPU Cooler [page 5-5](#)

## IEI Option

- **CB-USB02**  
Dual ports USB cable with bracket [page 5-6](#)
- **CF-502**  
Socket-7 CPU Cooler
- **CF-504**  
Slim Type Copper Socket-7/370 CPU Cooler [page 5-5](#)