




epic NANO-9452-R11

EPIC with Intel® Core™2 Duo/ Core™Duo/ Solo Processor, SATA, Dual PCIe GbE, CF Type II, IDE, USB 2.0 & Audio



Solder Side



FSB 667 DDR2 667 12V Only




Specifications

- ◆ CPU
Socket M Intel® Core™2 Duo, Core™ Duo/Solo processor with a 667MHz FSB
Celeron® M processor with a 533MHz FSB (Yonah Core)
- ◆ System Chipsets
Intel® 945GME + ICH7M
- ◆ BIOS
AMI BIOS
- ◆ System Memory
One 200-pin 667/533/400MHz DDR2 SDRAM SO-DIMM supported (system max. 2GB)
- ◆ Ethernet
Dual PCIe Broadcom BCM5787M GbE chipsets with ASF2.0 remote control support
- ◆ I/O Interface
6 x USB 2.0
2 x SATA
1 x IDE
3 x RS-232
1 x RS-232/422/485
1 x PS/2 for KB/MS
1 x LPT
1 x CF Type II
- ◆ Infrared Interface
1 x Infrared Interface by pin header
- ◆ Expansions
1 x PCI-104 (PCI bus)
- ◆ Super I/O
ITE IT8712F
- ◆ Digital I/O
8-bit digital I/O, 4-bit input/ 4-bit output by super I/O
- ◆ Audio
5.1 channel audio kit with Realtek ALC655 AC'97 codec
7.1 channel HD audio kit with Realtek ALC883 codec supports dual audio streams
- ◆ Display Interface
VGA Integrated in Intel® 945GME
Support HDTV resolution up to 1080i by component interface
18/24-bit dual-channel LVDS
- ◆ Watchdog Timer
Software programmable 1-255 sec. by super I/O
- ◆ Power Supply
12V only AT/ATX support
- ◆ Power Consumption
12V@3.01A (Intel Core™2 Duo 2.0GHz, 1GB 533MHz DDR2)
- ◆ Temperature
Operating: 0°C ~ 60°C (32 ~ 140° F)
- ◆ Humidity
Operating: 5% ~ 95% non-condensing
- ◆ Dimensions
165 mm x 115 mm

Features

1. Support Intel® Core™2 Duo, Core™Duo/ Solo processor with 667 MHz FSB
2. VGA integrated in Intel® 945GME supports 1080i HDTV-Out, 18/24-bit dual-channel LVDS
3. DDR2 667/533/400 MHz SO-DIMM socket supports up to 2GB
4. Dual PCIe Broadcom BCM5787M GbE chipsets with ASF2.0 remote control support

Dimensions (mm)



Packing List

1 x NANO-9452 Single Board Computer
2 x RS-232 Cable (P/N: 32200-000049-RS)
1 x IDE Cable (P/N: 32200-000009-RS)
1 x SATA Power Cable (P/N: 32100-088600-RS)
2 x SATA Cable (P/N: 32000-062800-RS)
1 x KB/MS Cable (P/N: 32000-000138-RS)
1 x Power Cable (P/N: 32100-087100-RS)
1 x Mini Jumper Pack
1 x Utility CD
1 x QIG (Quick Installation Guide)

Ordering Information

Part No.	Description
NANO-9452-R11	EPIC SBC, Intel® Core™2 Duo, Core Duo/ Solo FSB 667MHz with VGA/LVDS/HDTV-out, Dual PCIe GbE, SATA and Audio
32000-044300-RS	USB cable
32200-000077-RS	RS-232/422/485 cable
AC-KIT08R-R10	5.1 channel AC' 97 Audio Kit with Realtek ALC655 codec
AC-KIT-883HD-R10	7.1 channel HD Audio Kit with Realtek ALC883 codec support dual audio streams
CF-479B-RS	CPU cooler (50 mm x 50 mm x 26 mm, 50W)
32200-015100-RS	LPT cable
32100-043403-RS	ATX Power Cable
32000-083701-RS	HDTV out cable