



epic

NANO-GM45A2

EPIC SBC supports Intel® 45nm mobile Core™ 2 Duo processor with Intel® GM45 & ICH9M platform, DDR3/HDMI/IEEE1394




DDR3 support

Features

1. Socket P Intel® 45nm mobile Core™ 2 Duo processor support up to 1066MHz FSB
2. High performance MPEG-2 decoding, WMV9 (VC-1) and H.264 (AVC) supported
3. DDR3 1066/800MHz dual channel DDR3 supported up to 4GB
4. 18/24-bit dual channel LVDS/Analog CRT/HDTV output/HDMI supported
5. Support 4 x COM, 4 x USB, 2 x SATAII, 2 x IEEE 1394a and Audio
6. IEI One Key Recovery solution allows you to create rapid OS backup and recovery

Dimensions (mm)



CB-IEEE1394-RS Included

One Key **F3** Recovery



Specifications

- ◆ CPU
 - Socket P Intel® Core™ Duo Processor with a 1066/800MHz FSB
 - Socket P Intel® Celeron® M Processor with a 667/800 MHz FSB
- ◆ System Chipset
 - Intel® GM45/ICH9M
- ◆ BIOS
 - AMI BIOS
- ◆ System Memory
 - Two 204-pin 1066/800/667 MHz DDR3 SDRAM SO-DIMM supported (system max. 4GB)
 - Support for DDR3 at 667MHz when FSB at 667MHz only
- ◆ Ethernet Chipset
 - Dual Realtek 8111CP GbE Chipsets
- ◆ I/O interface
 - 4 x USB2.0 2 x SATAII 4 x RS-232
 - 2 x IEEE 1394a ports up to 400Mbps data transfer by VIA VT6315N
- ◆ Display Interface
 - Intel® Gen 5.0 integrated graphics engine with Mobile Intel® GMA 4500MHD
 - High Performance MPEG-2 Decoding, WMV9 (VC-1) and H.264 (AVC)
 - Microsoft DirectX®10 support
 - Analog CRT resolution up to 2048x1536
 - 18/24-bit dual channel LVDS resolution up to 1920x1200
 - HDTV-out resolution up to 1920x1080i by component interface
 - HDMI Port support up to 1080i/p
- ◆ Expansions
 - PCIe mini card
- ◆ Audio
 - Realtek ALC888 HD Audio
- ◆ WDT
 - Software programmable supports 1 ~ 255 sec. system reset
- ◆ Power Supply
 - 12V only, AT/ATX supported
- ◆ Power consumption
 - 12V@3.06A (Intel® Core™2 Duo T9400 2.53GHz, 1GB DDR3 1066 MHz)
- ◆ Temperature operation: -10°C ~ 60°C
- ◆ Humidity operation: 5% ~ 95 non-condensing
- ◆ Dimension
 - 165 mm x 115 mm
- ◆ Weight
 - GW: 700g NW 350g

Packing List

1 x NANO-GM45A2 Single Board Computer	
1 x Dual Port IEEE1394 Cable (P/N: CB-IEEE1394-RS)	
1 x Quad RS-232 Cable (P/N: 32100-147900-RS)	
1 x Mini Jumper Pack	1 x Power cable (P/N: 32100-087100-RS)
2 x SATA Cable (P/N:32000-062800-RS)	1 x Audio Cable (P/N: 32000-072100-RS)
1 x Utility CD	1 x QIG

Ordering Information

Part No.	Description
NANO-GM45A2-R10	EPIC SBC supports Intel® 45nm mobile Core™ 2 Duo processor with Intel® GM45 & ICH9M platform, DDR3, dual GbE, LVDS/CRT/HDTV-out, SATAII, USB2.0
CF-479B-RS	CPU Cooler
CF-479F-RS	CPU Cooler for T9400
32000-083702-RS	HDTV Cable Set with S-Video, Composite and Component Interfaces
32102-000100-100-RS 32102-000100-200-RS	SATA Power Cable
32000-114001-RS	SATA 5V power output Cable Kit for NANO series, SATA Cable 20cm, Power Cable 20cm
32100-043403-RS	ATX Power Cable