



KINO-LUKE


Mini ITX Motherboard with VIA LUKE 1GHz/533MHz CPU, CRT, Dual GbE, SATA, USB 2.0, COM and Audio



ILUKE-LVDS



Dual 18/24-bit LVDS Module



Feature

1. Mini ITX form factor with VIA LUKE processor
2. DDR 400/333MHz DIMM socket support up to 2GB
3. 36-bit TTL and optional dual 18/24-bit LVDS support
4. Dual RTL8110SC for GbE, SATA, USB 2.0, COM and Audio

Specification

DDR400

DDR333

Dual Display

SERIAL ATA

HI-SPEED CERTIFIED USB


Gigabit Ethernet

Windows Embedded

- ◆ **CPU**
 - VIA LUKE 1GHz
 - VIA LUKE 533MHz
- ◆ **System chipset**
 - VT8237R+
- ◆ **BIOS**
 - AMI BIOS Label
- ◆ **System Memory**
 - 2 x DDR 333/400MHz DIMM socket support up to 2GB
- ◆ **Ethernet**
 - Dual RTL8110SC for GbE
- ◆ **I/O**
 - 2 x SATA-150
 - 2 x IDE
 - 1 x LPT
 - 1 x PS/2 Mini DIMM for KB/MS
 - 5 x RS-232, 1 x RS-232/422/485
 - 8 x USB 2.0 (4 in rear & 4 by pin header)
- ◆ **Extension**
 - 1 x PCI
- ◆ **Audio**
 - AC'97 2.3 Realtek ALC655
- ◆ **Digital I/O**
 - 4 input / 4 output by super I/O
- ◆ **IrDA**
 - 1 x IrDA

- ◆ **Super I/O**
 - W83697HG
- ◆ **Display**
 - CRT
 - Integrated in VIA LUKE
 - TTL
 - 36-bit TTL support
 - LVDS (Optional)
 - Dual 18/24-bit LVDS by ILUKE-LVDS
- ◆ **Watchdog Timer**
 - Software programmable supports 1-255 sec. by super I/O
- ◆ **Power Supply**
 - ATX support
- ◆ **Power Consumption**
 - 5V@4.09A, +12V@0.56A, 5Vsb@0.19A
 - (VIA LUKE 1GHz FSB 133MHz, DDR 400 1GB SDRAM) -- 3D MARK
- ◆ **Temperature**
 - Operation: 0 ~ 60° C (32 ~ 140° F)
- ◆ **Humidity**
 - Operation: 5% ~ 95%, non-condensing
- ◆ **Dimension**
 - 170 mm x 170 mm
- ◆ **Weight**
 - GW: 950 g; NW: 380 g

Dimension



Packing List

1 x KINO-LUKE Single Board Computer	1 x I/O Shielding (P/N: 41005-0158C0-00-RS (VGA))
1 x ATA66/100 Flat Cable (P/N: 32200-000052-RS)	1 x I/O Shielding (P/N: 41005-0159C0-00-RS (DVI))
2 x SATA Cable (P/N: 32000-062800-RS)	1 x Mini Jumper Pack
1 x SATA Power Cable (P/N: 32100-088600-RS)	1 x Utility CD
1 x Dual RS-232 Cable (P/N: 32200-028401-RS)	1 x QIG (Quick Installation Guide)

Ordering Information

Part No.	Description
KINO-LUKE-533-R10	Mini-ITX VIA LUKE 533MHz Processor, CRT/LCD, Dual GbE, SATA and Audio
KINO-LUKE-1G-R10	Mini-ITX VIA LUKE 1GHz Processor, CRT/LCD, Dual GbE, SATA and Audio
KINO-LUKE-533DVI-R10	Mini-ITX VIA LUKE 533MHz Processor, DVI, Dual GbE, SATA and Audio
KINO-LUKE-1GDVI-R10	Mini-ITX VIA LUKE 1GHz Processor, DVI, Dual GbE, SATA and Audio
ILUKE-LVDS-R10	I-LUKE LVDS Module with Dual 18/24-bit Channel LVDS Support
32200-000077-RS	RS-232/422/485 Cable
CB-USB02A-RS	USB Cable
32200-000009-RS	ATA33 44p/44p Flat Cable



Headquarters

IEI Technology Corp.

TEL : +886-2-86916798 FAX : +886-2-66160028
 sales@ieiworld.com www.ieiworld.com
 No. 29, Jhongsing Rd., Sijhih City, Taipei County, 221, Taiwan

America-United States

IEI Technology USA Corp.

TEL : +1-562-690-6677 FAX : +1-562-690-0898
 sales@usa.ieiworld.com www.usa.ieiworld.com
 515 N. Puente St., Brea, CA 92821

China

Armorlink SH Corp.

TEL : +86-021-54429000 FAX : +86-021-54429100
 sales@ieiworld.com.cn www.ieiworld.com.cn
 No.515, Shenfu Road, Minhang District, Shanghai, China